


CABLES / KÁBLE

6. SPECIAL CABLES / RK 2xm



Speaker cables



6. Special cables

Application:

Cable is intended for audio transmission between amplifier and speaker interior sound system. Low cable capacity guarantee undistorted transmission of high sound frequencies.

Cable construction:

- **Core:** stranded Cu core, cross-sections 0,5; 0,75; 1,0 and 1,5 mm²
- **Conductor insulation:** PE
- **Covering:** Special transparent PVC

Marking:

- **Colour of the conductors:** blue, red

Technical data:

Core cross-section	[mm ²]	0,5	0,75	1,0	1,5
Informative dimensions (height x width)	[mm]	3 x 5	3,5 x 6	4,5 x 7,5	5 x 8,5
Effective resistance of conductors	[Ω/km]	40,1	26,7	20,0	13,7
Mutual capacitance	[pF/m]	67	67	67	67



The information supplied on this data sheet complies with our current level of knowledge by the date of publication. These information can be revised if there are any new knowledge and experiences available. Stated data are valid only for VUKI products. Any data changes in this documentation are restricted. Values in this documentation consider as informative data.

VUKI a.s., Rybníčná 38, SK - 831 07 Bratislava, Tel.: +421 2 4488 9906, Fax: +421 2 4488 2927
e-mail: vuki@vuki.sk, www.vuki.sk

